

PRIMERGY TX120

Mono socket Dual-Core Tower Server - Leading edge energy and space saving technologies at quietest operation

Issue November 22, 2007

Pages 2

PRIMERGY TX Tower Servers ensure energy efficient, carefree and continuous operation with proven data center technology. Their design for maximum ease of use and ease of management has been honored with industry design awards. The latest processor generation combined with innovative air flow cooling technology ("Cool-safe™") assure a long life and the highest possible performance at work. And as your business grows, so do our PRIMERGY towers, providing plenty of headroom for expansion so that you benefit longer from your investments in PRIMERGY tower servers.

For corporate workgroups and remote sites, PRIMERGY TX servers ensure less troubleshooting and lower costs with their complete PRIMERGY ServerView Suite remote management functions – flexible management from anywhere at any time.

The flexible custom supply model and our build-to-order process mean that only fully built and pre-tested solutions are shipped to customers, who can select from a broad family of tower models to meet their individual needs.

PRIMERGY TX120

The new first generation ultra-compact sized PRIMERGY tower server TX120 with a powerful Intel® Xeon® UP Dual-Core processor incorporates leading edge, low power consumption and space-saving technologies. Thus a significantly smaller footprint, reduced noise and energy savings are achieved. The PRIMERGY TX120 tower server is perfect for office workspaces, for distributed and SOHO applications including retail in-store, back office servers and small office application servers. Enhance your efficiency when it comes to simultaneous execution of multiple applications and downloading mass data. The processor with the Intel® 3000 chipset also supports VT technology.

Two 2.5-inch SAS hot-plug hard disks and the built-in RAID 1 functionality offer high data security. The standard iRMC (Integrated Remote Management Controller) offers enhanced system management, based on IPMI 2.0 technology, and the advanced diagnostic functions with Diagnostic LED increases operational reliability. A DAT drive can also be installed for easy backup or optional two further hot-plug hard disks. Alternatively an even more power saving Celeron® processor rounds off the offering.



| Benefits | Key Features |
|---|--|
| <ul style="list-style-type: none"> World class standard in energy saving reduces TCO with ca. 40% lower power consumption versus other standard tower servers | <ul style="list-style-type: none"> Active power reduced: down to 163 Watts fully equipped, even lower with Celeron® processor |
| <ul style="list-style-type: none"> World's smallest footprint, installable in office workspaces for fewer concerns about a lack of space (HxWxD 340 x 99 x 399 mm) | <ul style="list-style-type: none"> Reduced space and size: 1/3 smaller footprint & 1/4 less volume, compared to current 1-socket servers in the market achieved by downsizing the heat pipe and adopting 2.5 inch HDD |
| <ul style="list-style-type: none"> Absolutely quiet system (idle 28 dB and operation 31 dB), thus optimized for use in offices | <ul style="list-style-type: none"> Advanced cooling technologies such as "heat-pipe" cooling and "straight-line cooling" achieve a low noise level equivalent to a whispering voice |
| <ul style="list-style-type: none"> A real reliable and powerful server nevertheless! | <ul style="list-style-type: none"> Raid 1 & hot-plug HDD, ECC memory, Server processor Xeon UP, Server Operating System, integrated Remote Management Controller (iRMC) with advanced Pack option |

| | |
|--|---|
| Type | Mono Socket Tower Server |
| System board | D2550 |
| Chip set | Intel® 3000 |
| Processors | Intel® Celeron® Intel® Xeon® UP(Dual-Core) |
| Type / Frequencies (GHz) | 440 (2.00) 35W/ 3040(1.86) / 3070 (2.66) 65W |
| Front-Side-Bus | 800 / 1066 MHz |
| Second-Level-Cache | 512 KB / 2 MB / 4 MB, ECC |
| Memory | 512 MB up to max. 8 GB |
| ECC PC2-5300 DDR2 SDRAM; 2 banks with 2 slots each; (512 MB, 1 GB, 2 GB modules) Mix and match possible; with dual channel operation better performance (2 capacity equal modules necessary). Single channel (1 module) configuration possible. | |
| Flash-EPROM | |
| Local BIOS update with floppy disk; Remote BIOS-Update via LAN with Global Flash and service partition | |
| Interfaces | |
| Serial | 1 x serial RS-232-C (9-pin) |
| Keyboard, Mouse | 2 x PS/2 |
| USB 2.0 | 2 x front, 2 x back 1 x internal for backup drives |
| Graphics | 1 x VGA (15-pin) |
| LAN | 1 x RJ45, 1 x service LAN (10/100 Mbit/s) |
| Onboard controller ** | |
| IDE | 1 x ATA100 for optical drive |
| SAS (LSI 1064) | 4 port SAS for internal HDD's and internal backup devices with RAID 0, 1 (Integrated Mirroring Enhanced also for odd numbered HD's for Windows and Linux) |
| LAN (Broadcom BCM5754) | Ethernet 10/100/1000 Mbit/s (PXE-Boot via LAN from PXE server) |
| Server management | Integrated Remote Management Controller iRMC, IPMI 2.0 incl. graphics |
| Hard disk drives | 36, 73, 146 Gbyte 2.5-inch SAS (hot-plug) |
| 1 Gbyte equals one billion bytes when referring to hard disk drive capacity; accessible capacity may vary. | |
| I/O Slots: | |
| 1 x PCI-e x8 (x4 wired), low profile | |
| 1 x PCIe x1, low profile | |
| 1 x PCI 32Bit/33 MHz low profile (5V) | |
| Drive bays | |
| for hard disks | 2 x 2.5/1-inch, for hot-plug SAS (in slide-in chassis) + 2 HDD box optional, (occupies 3.5/1.6-inch drive bay) |
| for accessible drives | 1x 3.5/1.6-inch for tape or HDD option 1x 5.25/0.5-inch occupied with DVD or DVD-RW |

| | |
|---|---|
| Electrical values | |
| 1x standard power supply | |
| Output power | 250 W |
| Rated voltage range | 100 - 240 V |
| Rated frequency | 50-60 Hz |
| Max. rated current | 100 V - 240 V / 2A – 1A |
| Rated current in basic configuration | 100 V - 240 V / 1.63A – 0.69A |
| Active power | 163 W |
| Apparent power | 166 VA |
| Heat emission | 587 kJ/h (556 btu/h) |
| Temperature/Noise/Dimensions/Weight | |
| Ambient temperature | 10°C - 35°C (DIN IEC 721-3-3) class 3K2 |
| Declared noise in according with ISO 9296 | idle / operating |
| Sound pressure L _{pAm} | ≤ 28 db(A) / ≤ 31 db(A) |
| Sound power L _{WAd} | ≤ 4,0 B / ≤ 4.4 B (1 Bel = 10 db) |
| Dimension of floor-stand (HxWxD) | 340 * 99 * 399 mm (without feet) |
| Weight | approximately 10 kg (max.) |
| Compliance with Norms and Standards | |
| Product safety | |
| Global | IEC 60950-1 |
| Europe | EN 60950-1 |
| USA | UL 60950-1. |
| Canada | CAN/CSA-C22.2 No. 60950-1. |
| Electromagnetic compatibility | |
| This product and the released accessories, are in compliance with emission class A. In certain cases measures have to be taken to reduce the electro magnetic influence to other equipment. | |
| Europe | EN 55 022 class A, EN 55024, EN61000-3-2 / -3 |
| USA / Canada | FCC class A |
| Declaration of conformity | |
| Europe (CE) | 2004/108/EC 2006/95/EC |
| North America | FCC class A |
| Approvals | |
| Product safety | |
| Global | CB |
| Europe | CE |
| USA / Canada | CSA _{US} / CSA _C |
| There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons, can be applied for on request. | |
| Supported operating systems | |
| See actual release status operating systems : e.g. Windows 2003; Novell SUSE Linux Enterprise Server , Red Hat Enterprise Linux; VMware Infrastructure (Support of Debian, Ubuntu, Mandriva Linux and other Linux derivatives on demand) | |
| ** For supported controllers (onboard and PCI cards for SCSI, SAS, RAID, LAN, WAN, etc.), please refer to the corresponding system configurator. | |
| Server Management (see separate data sheets) | |
| Standard | PRIMERGY ServerView Suite; PDA, ASR&R |
| Optional | RemoteView, iRMC Advanced Pack |